



## NORAC

405 S. Motor Ave.  
Azusa, CA 91702  
P: 626.334.2908  
F: 626.334.3512  
[www.norac.com](http://www.norac.com)

Product Bulletin 8/16/2004

### COAD® LM CALCIUM STEARATE

#### DESCRIPTION

COAD® LM Calcium Stearate is a high grade calcium stearate manufactured under controlled conditions to provide a lower melting product than typical calcium stearates. It is useful in applications where limits on zinc content is critical and calcium is not objectionable.

#### TYPICAL PROPERTIES

Total Ash, % .....	9.8
Moisture, % .....	2.0
Free Fatty Acid, % .....	2.0
Soluble Salts, % .....	Nil
Softening Point, C .....	130
Apparent Density, lbs/ft <sup>3</sup> .....	28
Mean Particle Size, microns .....	11
Top Size %98, microns .....	35
% Thru 325 mesh .....	100

Appearance: Free flowing fine white powder.

## **APPLICATIONS**

- Rubber Processing: COAD® LM Calcium Stearate is used as a dusting agent on uncured rubber stocks to prevent adhesion.

## **STORAGE AND HANDLING RECOMMENDATIONS**

- Storage - Store at ambient temperatures away from sources of heat or from places of extreme moisture.
- Fire - Use water from a safe distance, preferably with a fog nozzle.
- Handling - Avoid contact with skin or eyes. Safety goggles are recommended.
- Spills - Clean up immediately. Sweep up and discard in a closed container.
- Disposal - Consult Federal, State, and Local regulations. Consult the telephone book or EPA for list of approved disposal companies.
- Other - See MSDS for COAD® LM Calcium Stearate for additional health, safety, and environmental information.

## **PACKAGING**

COAD® LM Calcium Stearate is packaged in 25 lb. and 50 lb. multiwall bags, unitized on non-returnable wooden pallets. Please contact your Norac sales representative to discuss your special packaging requirements.