



NORAC

405 S. Motor Ave.
Azusa, CA 91702
P: 626.334.2908
F: 626.334.3512
www.norac.com

Product Bulletin 8/16/2004

COAD® 23 ZINC STEARATE (Polymer Grade)

DESCRIPTION

COAD® 23 Zinc Stearate (Polymer Grade) was developed especially for the polymer industry with a low ash and low impurities for good melt clarity and heat stability. The medium particle size and moderately high bulk density enhances flow characteristics.

TYPICAL PROPERTIES

Total Ash, %	13.6
Moisture, %	0.2
Free Fatty Acid, %	0.2
Soluble Salts, %	Nil
Softening Point, C	120
Apparent Density, lbs/ft ³	25
Mean Particle Size, microns	11
Top Size %98, microns	35
% Thru 325 mesh	100

Appearance: Free flowing fine white powder.

APPLICATIONS

- Dry blends: COAD® 23 Zinc Stearate (Polymer Grade) reduces caking and improves flow properties. Due to its greater density, higher loadings can be obtained in certain equipment.

STORAGE AND HANDLING RECOMMENDATIONS

- Storage - Store at ambient temperatures away from sources of heat or from places of extreme moisture.
- Fire - Use water from a safe distance, preferably with a fog nozzle.
- Handling - Avoid contact with skin or eyes. Safety goggles are recommended.
- Spills - Clean up immediately. Sweep up and discard in a closed container.
- Disposal - Consult Federal, State, and Local regulations. Consult the telephone book or EPA for list of approved disposal companies.
- Other - See MSDS for COAD® 23 Zinc Stearate (Polymer Grade) for additional health, safety, and environmental information.

PACKAGING

COAD® 23 Zinc Stearate (Polymer Grade) is packaged in 25 lb. and 50 lb. multiwall bags, unitized on non-returnable wooden pallets. Please contact your Norac sales representative to discuss your special packaging requirements.