



**NORAC**

405 S. Motor Ave.  
Azusa, CA 91702  
P: 626.334.2908  
F: 626.334.3512  
[www.norac.com](http://www.norac.com)

Product Bulletin 4/1/2004

## **COAD® 33 ZINC STEARATE PRILL (Polymer Grade)**

### **DESCRIPTION**

COAD® 33 Zinc Stearate Prill (Polymer Grade) was developed especially for the polymer industry with a low ash and low impurities for good melt clarity and heat stability. The prilled particle size and high bulk density enhances flow characteristics and reduces dust.

### **TYPICAL PROPERTIES**

Total Ash, % .....	13.5
Moisture, % .....	0.2
Free Fatty Acid, % .....	0.3
Soluble Salts, % .....	Nil
Softening Point, C .....	122
Apparent Density, lbs/ft3 .....	35
% Thru 20 mesh, .....	100
% Thru 200 mesh .....	5

Appearance: Free flowing white micro beads.

## **APPLICATIONS**

- Dry blends: COAD® 33 Zinc Stearate Prill (Polymer Grade) reduces caking and improves flow properties while reducing dust. Due to its greater density, higher loadings can be obtained in certain equipment.

## **STORAGE AND HANDLING RECOMMENDATIONS**

- Storage - Store at ambient temperatures away from sources of heat or from places of extreme moisture.
- Fire - Use water from a safe distance, preferably with a fog nozzle.
- Handling - Avoid contact with skin or eyes. Safety goggles are recommended.
- Spills - Clean up immediately. Sweep up and discard in a closed container.
- Disposal - Consult Federal, State, and Local regulations. Consult telephone book or EPA for list of approved disposal companies.
- Other - See MSDS for COAD® 33 Zinc Stearate Prill (Polymer Grade) for additional health, safety, and environmental information.

## **PACKAGING**

COAD® 33 Zinc Stearate Prill (Polymer Grade) is packaged in 25 lb. and 50 lb. multiwall bags, unitized on non-returnable wooden pallets. Please contact your Norac sales representative to discuss your special packaging requirements.